



Telaris EARTH-TEST Earth Resistance Tester

The Telaris Earth-Test can test the ability of soil and grounding connection to conduct electricity and provide an electrical reference point. Good soil conductivity is needed to limit static electricity charge in potentially flammable situations and minimize the voltage difference between power return and earth ground for personal safety. Resistance testing is done by 2 wire, 3 wire or 4 wire testing methods.

- Earth resistance measurement
- Specific earth resistance measurement
- The integrated constant current measurement principle allows the application in sandy as well in rocky environments
- Monitoring and display of auxiliary earth and probe resistances
- Displays the actual test current
- Automatic and manual and frequency selection for noise reduction
- Test voltage pre-selection
- Clear and large digital display provides the user with an optimum visual indication of both test values and limits
- Auto power off
- Specific earth resistance measurement in compliance with the Wenner principle

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



**Telaris EARTH-TEST Earth Resistance Tester****Specifications**

Display	3 digit; LCD; 1999 Count	
Meas. Principle	Constant voltage / variable current measurement	
Earth Resistance	Range	0.05 to 19.99 Ω ; 20 to 199.9 Ω ; 200 to 1999 Ω
	Resolution	0.01 Ω ; 0.1 Ω ; 1 Ω
	Tolerance	$\pm(4\%$ rdg. + 2 digits)
Probe-aux. resistance	Range	0.1 to 50 k Ω
	Resolution	0.1 k Ω
	Tolerance	$\pm(10\%$ rdg. + 3 digits)
Test Current Display	Range	0.1 to 13 mA
	Resolution	0.1 mA
	Tolerance	$\pm(10\%$ rdg. + 3 digits)
Max. Test Current	approx. 12 mA	
Test Voltage	max. 25 V / 50 V AC selectable	
Frequency	127 Hz / 140 Hz selectable	
Safety Complying with	EN61010-1/DIN VDE 0411, EN61557-1,5/DIN VDE 0413	
Overvoltage category	CAT III / 300 V	
Pollution Degree	2	
Power Supply	6 x 1.5 V(AA), IEC LR6	
Dimensions	235 x 105 x 68 mm (9.3 x 4.1 x 2.7 in.)	
Weight (inc. batteries)	approx. 640g (1.4 lbs.)	

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

Amprobe Test Tools Europe
Beha-Amprobe GmbH
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools. All rights reserved.
10/2008 3393515 Rev A